



2220 Centre Park Court
 Stone Mountain, GA 30087
 Toll Free: (800) 342-4874
 Fax: (770) 879-3511
 www.4tsi.com

Special Mac Valves For the Sawmill Industry



6300 Series

6313D-000-PM-113DA=3220



Indicator light for trouble-shooting
 Manual, extending, non-locking override

Part # Breakdown

- 6313D: Single solenoid
- 6313D: Indicator light
- 000: Valve body only, base not included
- PM: Pilot exhaust, muffled
- 113DA: AC voltage 110/120
- 113DA: Manual, extended, non-locking override
- 113DA: Electrical connection plugs in to base (standard)
- =3220: Special grease and rubber compound designed to resist water absorption and eliminate swelling and sticking

6500 Series

6513B-000-PM-113DA=3220



Indicator light for trouble-shooting
 Manual, extending, non-locking override

Part # Breakdown

- 6513B: Single solenoid
- 6513B: Indicator light
- 000: Valve body only, base not included
- PM: Pilot exhaust, muffled
- 113DA: AC voltage 110/120
- 113DA: Manual, extended, non-locking override
- 113DA: Electrical connection plugs in to base (standard)
- =3220: Special grease and rubber compound designed to resist water absorption and eliminate swelling and sticking

82 Series

82A-AC-000-TM-DAAP-3DA=4910



Manual, extending, non-locking override
 Indicator light for trouble-shooting

Part # Breakdown

- 82A-AC: Single solenoid, plug-in body w/indicator light
- 000: Valve body only, base not included
- TM: Pilot exhaust muffled
- DAAP: AC voltage 110/120
- 3DA: Manual, extended, non-locking override
- 3DA: Electrical connection plugs in to base (standard)
- =4910: Special grease and rubber compound designed to resist water absorption and eliminate swelling and sticking

Notes

- Dual pressure valves are available. Please contact customer service for assistance.
- Individual and manifolding subbases are available for all valve series. Please contact customer service for assistance.
- Water resistant modifications are available for **all** valve series. Please contact customer service for assistance.
- All valves listed above are available in additional voltages upon request, e.g. 24VDC.